


DUCTILITY MACHINE

ASTM D 113, D 5976 - IP 32 - ISO 1208

EN 13398, 13589, 13703

The apparatus consists of a constant temperature bath capable to work in the range from -10 to 40 °C (thanks to a built-in cooling compressor) with an electrically powered tractor that pulls apart at a determined speed the two ends of two briquet specimens: the elongation is measured by means of a pointer on the tractor and a graduated scale fixed to the cover.



Apparatus

- Enamel finished steel case, floor mounted with swivelling castors.
- Stainless steel bath thermally insulated: complete with drain valve.
- Chromium plated brass pump: it provides an adequate stirring of the liquid in the bath.
- Stainless steel heater.
- Microprocessor thermoregulator with PID action: built-in digital display 0.1°C accuracy. Probe: Pt100 RTD. Working range: from -10 to 40°C.
- Safety device against overheating and low level with alarm lamp.
- Built-in hermetic cooling compressor: CFC/HCFC-free gas.
- Acrylic hinged cover: it helps to maintain a constant temperature in the bath providing a clear view of the inside.
- Traction carriage with two-speed motor for 10 and 50 mm/min: the carriage supports 2 briquet molds. Automatic stop safety switch that stops the carriage when the maximum elongation has been reached. Traction length: 50, 100 or 150 cm.
- White screen fixed to the bottom of the bath: it permits a more clear vision of the elongated specimen during the test.
- Easy access control box containing all the electronics: anodized aluminium control panel with english written indications.
- English written user manual with installation instructions.
- For 220 V/50 Hz connections: 1800 W power consumption.
- Dimensions (l x w x h): mm 1800 x 450 x 1300 approx (AD0113-200) mm 2400 x 450 x 1300 approx (AD0113-250). Weight: 250 kg approx.
- CE marked.

AD0113-100	Apparatus, 50 cm traction length
AD0113-110	Apparatus, 100 cm traction length
AD0113-120	Apparatus, 150 cm traction length

ACCESSORIES

AD0113-A00	Mold acc. to ASTM D 113 - IP 32 - IS 1208
AD0113-A01	Brass plate for mold assembling
AD5976-A00	Mold acc. to ASTM D 5976
CAL001	PT100 simulator
CAL003	Official Certificate for Pt100 simulator

Specifications may vary without notice.

The apparatus includes the items listed aside the picture, accessories etc. should be purchased separately.



Dott. Gianni Scavini & C.

Via Donne della Resistenza, 26 - 28831 Baveno (VB) Italy
Tel. +39-0323-924134 Fax +39-0323-924935
www.scavini.com